

15LB075-UW / 15LB300-4ohm

BETA 3



Features

- >Nominal OD: 15"
- >Die-casting aluminum basket
- >Cloth edge
- >75mm copper cladding aluminum voice coil
- >Nominal Impedance: 4ohm
- >Power rating: 350W



Specifications :

;; Throat diameter	;; 15"/388 inch/mm
;; Impedance	;; 4Ohm
;; Pink Noise power	;; 350W
;; Instantaneous power	;; 700W
;; Sensitivity	;; 95.9 dB/W/m
;; Frequency response	;; 34-3.5KHz
;; Voice coil diameter	;; 75mm
;; Voice coil material	;; BKSV
;; Former material	;; KAPTON
;; Cone material	;; Cone paper with cloth edge
;; Basket material	;; Die-casting aluminum
;; Magnet	;; Y30
;; Resonance frequency	;; 33.8Hz
;; Qms	;; 10.33
;; Qes	;; 0.35
;; Qts	;; 0.33
;; Vas	;; 231Litres
;; Mms	;; 117.8grams
;; Re	;; 3.7Ohm
;; Sd	;; 881cm ²
;; Xmax	;; 1.5mm
;; Cms	;; 0.19mm/N
;; BL	;; 16.4T.m
;; Le	;; 1.3mH
;; Overall diameter	;; 388mm
;; Diagram diameter	;; 340mm
;; Magnet diameter	;; 190mm
;; Bolt circle diamete	;; 370mm
;; Depth	;; 164.5mm
;; Net weight	;; 7.8kg